

Extrusion coating line Hanyoung

Gebrauchtmaschine | Artikel-Nr. 4538

Technische Daten:

| | |
|-------------|---------------------------------|
| Maschine: | Extrusion coating line Hanyoung |
| Hersteller: | Hanyoung |
| Typ: | Extrusion coating line |
| Größe: | None |
| Kapazität: | None |
| Jahr: | None |



Beschreibung:

Extrusion coating line with 2 separate extruders fully automatic operation

Automatic splicing for rewinder/unwinder 2 coronas

Material:

- Paper up to 150gsm,
- Film PP, PET, BOPP, PVC up to 250mic Coating material : All polymers

Speed: 250m/min

Used occasionally the last 7 years

MAJOR REFIT AND UPGRADE IN 2009 with DIGITAL EUROTHERM DRIVES

Excellent condition European electronics

The machine has produced :

PET + PE

PET + PE + ALU + PE PAPER + PE

PAPER + PE + ALU + PE

Other details:

Web width max.: 1500mm Heating source for drying : Steam

- Unwinder.
 - Type: Double shaft
 - Automatic splicer
 - Diam. Max.: 1000mm
 - Core diam. : 76mm (3 inches) ,150mm (6 inches) with adaptors
 - Control tension type : Automatic
- Auxiliary unwinder
 - Type: Double
 - Diam. Max. :550mm
 - Core diam. :76mm (3 inches) ,150mm (6 inches) with adaptors
 - Control tension type :Automatic
- Extruders:
 - Screw diam :90
 - Output capacity (Kg/h) : 140Kg/h
- T- Die: 1500mm
 - Maker : HANYOUNG
 - Die opening : Yes
 - Die gap range : 5mic to 35mic