

# CASMATIC Bundler CMB 150

## Gebrauchtmaschine | Artikel-Nr. 5652

### Technische Daten:

Maschine:	CASMATIC Bundler CMB 150
Hersteller:	CASMATIC S.p.a
Typ:	CMB 150
Größe:	None
Kapazität:	None
Jahr:	None



## Beschreibung:

---

### Technical details:

Infeed: Automatic

Operation: Electro-mechanical/pneumatic

Max. machine speed: 14 cycles/min.

Max. production speed: 13 cycles/min.

Roll infeed height: 770 mm

Pack exit height: 1150 mm

Weight: 5500 kg (approx)

Av. size change-over time: 35 min. (approx) 2 Operators

Av. size adjustment time: 20 min. (approx) 2 Operators

Roll change time: 5 minutes

Ambient conditions

- Temperature from +5 to +40°C
- Relative humidity Max. 70%

### PNEUMATIC SYSTEM

Air pressure: 6 bar

Compressed air consumption Max.: 800 NI/min

### ELECTRICAL SYSTEM (STANDARD)

Installed power: 23.5 KVA

Standard voltage: 3x380/415/440 V (+/- 5%) + earth

Voltage variation: +/- 5%

Frequency: 50/60 Hz

Neutral wire: None

Electrical cabinet voltage: 220 V AC

PLC I/O card voltage

- Inputs/outputs 24 V DC
- Solenoid valve outputs 24 V DC
- Contactor outputs 24 V DC

### PRODUCTS TO BE PACKED

Pack height (H) from 95 to 305 mm

Pack width (W) from 95 to 560 mm

Pack length (L1) from 190 to 560 mm

### FINISHED PACKAGE DIMENSIONS

Pack width (W): From 330 to 780 mm

Max.: 850 con H 250mm

Max.: 700 con H 345mm

Max.: 720 con H 400mm

Pack length: (L) From 200 to 800 mm

Pack height: (H) From 195 to 305 mm

400 mm (Optional)