

CASMATIC Bundler CMB 150

Gebrauchtmachine | Artikel-Nr. 5652

Technische Daten:

Maschine:	CASMATIC Bundler CMB 150
Hersteller:	CASMATIC S.p.a
Typ:	CMB 150
Größe:	None
Kapazität:	None
Jahr:	None



Beschreibung:

Technical details:

Infeed: Automatic

Operation: Electro-mechanical/pneumatic

Max. machine speed: 14 cycles/min.

Max. production speed: 13 cycles/min.

Roll infeed height: 770 mm

Pack exit height: 1150 mm

Weight: 5500 kg (approx)

Av. size change-over time: 35 min. (approx) 2 Operators

Av. size adjustment time: 20 min. (approx) 2 Operators

Roll change time: 5 minutes

Ambient conditions

- Temperature from +5 to +40°C
- Relative humidity Max. 70%

PNEUMATIC SYSTEM

Air pressure: 6 bar

Compressed air consumption Max.: 800 NI/min

ELECTRICAL SYSTEM (STANDARD)

Installed power: 23.5 KVA

Standard voltage: 3x380/415/440 V (+/- 5%) + earth

Voltage variation: +/- 5%

Frequency: 50/60 Hz

Neutral wire: None

Electrical cabinet voltage: 220 V AC

PLC I/O card voltage

- Inputs/outputs 24 V DC
- Solenoid valve outputs 24 V DC
- Contactor outputs 24 V DC

PRODUCTS TO BE PACKED

Pack height (H) from 95 to 305 mm

Pack width (W) from 95 to 560 mm

Pack length (L1) from 190 to 560 mm

FINISHED PACKAGE DIMENSIONS

Pack width (W): From 330 to 780 mm

Max.: 850 con H 250mm

Max.: 700 con H 345mm

Max.: 720 con H 400mm

Pack length: (L) From 200 to 800 mm

Pack height: (H) From 195 to 305 mm

400 mm (Optional)