

Double layer paper machine 4640 mm trimmed w. Gebrauchtmaschine | Artikel-Nr. 6252

Technische Daten:

Maschine:	Double layer paper machine 4640 mm trimmed w.
Hersteller:	KMW Carcano
Typ:	Double ply fourdrinier Maschine
Größe:	4.64 meters trimmed width
Kapazität:	115-200 GSM and max. speed 750 m/min with Production: ca. 800 Tons per day
Jahr:	regularly updated



Beschreibung:

Top headbox: 5180 mm outlet

Bottom headbox: 5000mm outlet

GSM range: 115-200 g/m²

Speed: upto 720 m/min.

Max. drive speed: 750 m/min.

Width after rewinder: 4640 m

Production type: Brown paper for container board

Press section: 2 Presses

Press 1: Uni Press : 70Kg/cm

Press 2: High impulse Press: 300kg/cm

Cylinder dryers: 46 preheating section, 20 post dryers, 66 in total

Design speed: 1000m/min.

Starch press: roll dia: 700mm and 950 mm

QCS: Manufacturer: Voith, year 2010s

With rewinder

Stock preparation

Stock Preparation Line (Optional)

The stock preparation line is composed by

- a set of high-density Cyclones,
- 2 stages of coarse screening process.

The stock for each ply is treated also with 3 stages of fine screening.

High Density Cyclon D2C-S Voith 4

Coarse Screening FS3B Escher Wyss 1

Coarse Screening FS2B Escher Wyss 1

Fine Sceening (Botom Ply) Sund Defbrator T9 Metso Paper 1

Fine Sceening (Botom Ply) Sund Defbrator T6 Metso Paper 2

Fine Sceening (Top Ply) Sund Defbrator T9 Metso Paper 1

Fine Sceening (Top Ply) Sund Defbrator T6 Metso Paper 2

Thickener Augers M70 Maule 8

Refners Major 30 " Black Clawson 1